KØSTER

Tested and certified

- CO2-Permeability (DIN EN 1062-6)
- Properties of solar reflectance, ("Solar Reflectance Index")
- CE-Certification (EN 1504-2)







KÖSTER at your service – worldwide.













// Contact us

KÖSTER BAUCHEMIE AG Dieselstraße 1–10 \cdot 26607 Aurich

Tel.: +49 4941 9709 0 E-Mail: info@koster.eu

www.koster.eu

Follow us on social media:











Fields of Application

- · Indoor and outdoor application
- Basement waterproofing
- Roof waterproofing
- Waterproofing under tiles

- Balconies and terraces
- Waterprofing of tanks and basins
- Carbonisation inhibiting
- · Renovation of old bituminous waterproofing

// Application





4 KÖSTER Superfleece is applied into the fresh first layer



Fillet installed with KÖSTER Repair Mortar



5 Second layer of KÖSTER 21



3 First layer of KÖSTER 21



6 Final result









Key features of KÖSTER 21

- Elastic and crack-bridging
- For indoor and outdoor application
- resistant to UV-radiation
- resistant to salt
- resistant to hydrolysis and freeze / thaw effects
- Good adhesion to slightly moist mineral substrates
- Good adhesion e.g. to concrete, metal, PVC or old bituminous waterproofing
- Easy to apply
- Resistant to pressurized water
- Hydrophobic (water repelling effect)
- Free of solvents and volatile organic compounds (VOC)
- Does not contain isocyanates or bitumen
- 2-component, fast-curing
- White color, reflects thermal radiation (saves energy)
- Versatile application per brush, trowel, roller, or spraying

